



# NTN BEARING USA CORP.

2.938 Inch | 74.625 Millimeter x 3.5 Inch | 88.9 Millimeter x 3.25 Inch | 82.55 Millimeter DODGE SP4B-IP-215R Pillow Block Bearings



Bearing No. SP4B-IP-215R

SP4B-IP-215R Bearing 2D drawings and 3D CAD models

|                           |  |
|---------------------------|--|
| Category                  | Pillow Block Bearings  |
| Inventory                 | 0.0  |
| Manufacturer Name         | ABB MOTORS AND MECHANICAL INC  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 11.13  |
| EAN                       | 0782476364670  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Adapter Sleeve   |
| Housing Style             | 4 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 5/8 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | INS-IP-215R  |
| Seals                     | Triple Lip Contact   |
| Housing Configuration     | 1 Piece Solid  |
| Inch - Metric             | Inch   |
| Other Features            | Double Row   Has Flinger   |
| Long Description          | 4 Bolt Pillow Block; 2-15/16" Bore; 3-1/4" Base to Center Height; Adapter Sleeve Mount; Spherical Roller Bearing; 7-15/16" |



## NTN BEARING USA CORP.

|                               |   |
|-------------------------------|---|
|                               | Minimum Bolt Spacing;<br>8-5/16" Bolt Spacing<br>Maximum; Relub |
| Category                      | Pillow Block  |
| UNSPSC                        | 31171511  |
| Harmonized Tariff Code        | 8483.20.40.80   |
| Noun                          | Bearing   |
| Keyword String                | Pillow Block  |
| Manufacturer URL              | <a href="http://www.dodge-pt.com">http://www.dodge-pt.com</a>   |
| Manufacturer Item Number      | SP4B-IP-215R  |
| Manufacturer Internal Number  | 071711  |
| Weight / LBS                  | 24.51   |
| Nominal Bolt Center to Center | 8.1 Inch   206.4 Millimeter                                     |
| Bolt Spacing Minimum          | 7.938 Inch  <br>201.625Millimeter                               |
| B                             | 3.25 Inch   82.55 Millimeter                                    |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter  |
| D                             | 3.5 Inch   88.9 Millimeter                                      |
| Bolt Spacing Maximum          | 8.313 Inch  <br>211.15Millimeter                                |
| d                             | 2.938 Inch   74.625<br>Millimeter                               |